

SolaMaster® Series Material Specifications:

Roof Dome: Outer dome is UV and impact resistant for extended life. Injection molded acrylic classified as CC2 material, 0.125 in (3.2 mm) thick, with visible light transmission of 92% and ultra violet light transmission of 0.03%. Patented Raybender® 3000 Technology (variable prism optic molded into dome) to capture low angle sunlight and limit high angle sunlight.

Optional Inner Dome:

Injection molded acrylic classified as CC2 material, 0.115 in (3 mm) thick to meet ENERGY STAR requirements

Injection molded polycarbonate classified as CC1 material, 0.115 in (3 mm) thick to meet ENERGY STAR and High Velocity Wind Zone requirements.

Permeable dome seal: Adhesive backed weatherstrip locks out dust and bugs, but allows moisture to escape.

Dome ring to prevent thermal bridging between base flashing and tubing and channel condensed moisture out of tubing. Injection molded high impact PVC.

Dome ring seal: Butyl glazing rope to minimize air infiltration.

Roof Flashing Base: One piece, seamless, leak-proof flashing functioning as base support for dome and top of tube.

Flashing Options: 4-in, 8-in 11-in high (100 mm, 200 mm, 280 mm) or curb cap with inside dimensions 27 in x 27 in (685 mm x 685 mm) to cover curb by others.

Reflective Tube: Aluminum sheet, thickness 0.018 in (0.5 mm)

24 in (600 mm) extension tube or optional 30 degree adjustable tube. Optional 0-90 degree extension tube kit also available.

Spectralight® Infinity material, fabricated from aluminum sheet meeting ASTM B 209 requirements, alloy and temper required by the manufacturer to suit forming operations and finish requirements.

Interior Finish: Spectralight Infinity high reflectance specular finish on exposed reflective surface. Specular reflectance for visible spectrum (400 nm to 760 nm) greater than 99 percent. Total solar spectrum reflectance (400 nm to 2500 nm) less than 93 percent.

Color: a* and b* (defined by CIE L*a*b color model) shall not exceed plus 2 or be less than minus 2 as determined in accordance to ASTM E 308.

Diffuser Assembly: Diffuser attached directly to bottom of 24 in (600 mm) extension tube. Diffuser trim ring injection molded acrylic (white). Open cell foam diffuser seal to minimize dust and bug infiltration.

Diffuser Options: OptiView® Diffuser or Prismatic Diffuser.

